

DIN 912 Socket Head Cap Screw

Diameter	M2	M2.5	M3	M4	M5	M6	M8	M10	M12	M14	M16	M18	M20	M22	M24	M30	M36	M48
Length																		
3	0.155																	
4	0.175	0.345																
5	0.195	0.375	0.7															
6	0.215	0.405	0.7	1.5														
8	0.255	0.465	0.8	1.7	2.5													
10	0.295	0.525	0.9	1.8	2.7	4.7												
12	0.355	0.585	1.0	2.0	3.0	5.1	10.9											
16	0.415	0.705	1.2	2.3	3.5	5.8	12.1	20.9										
20	0.495	0.825	1.4	2.7	4.0	6.5	13.4	22.9	32.1									
25		0.975	1.6	3.2	4.8	7.6	15.0	25.4	35.7	48	71.3							
30			1.9	3.7	5.6	8.3	16.9	27.9	39.3	53	77.8	111	128					
35				4.2	6.3	9.9	18.9	30.4	42.9	58	84.4	120	139	211				
40				4.7	7.1	11.0	20.9	32.9	46.5	63	91	129	150	224	270			
45					7.9	12.1	22.9	36.1	50.1	68	97.6	138	161	237	285	500		
50					8.6	13.2	24.9	39.3	54.5	73	106	147	172	250	300	527		
55						14.3	26.9	42.5	58.9	78	114	156	183	263	316	554	870	
60						15.4	28.9	45.7	63.4	84	122	165	194	276	330	581	910	
65							31.0	48.9	67.8	90	130	174	205	291	345	608	950	
70							33.0	52.1	71.3	96	138	183	216	306	363	635	990	2040
80							37.0	58.5	80.2	108	154	203	241	336	399	690	1070	2180
90								64.9	89.1	120	170	223	266	366	435	745	1150	2320
100								71.2	98.0	132	186	243	291	396	471	800	1230	2460
110									107.0	144	202	263	316	426	507	855	1310	2600
120									116.0	156	218	283	341	456	543	910	1390	2740
130										168	234	303	366	486	579	965	1470	2880
140										180	250	323	391	516	615	1020	1550	3020
150											266	343	416	546	651	1080	1630	3160
160											282	363	441	576	687	1130	1710	3300
180												403	491	636	759	1240	1870	3590
200													541	696	831	1350	2030	3870
220														756	903	1460	2190	4150
240															975	1570	2250	4430
260																1680	2410	4710
280																1790	2570	4990
300																1900	2730	5270

